

# Product Data Sheet



*Premium Lubricant Products, Optimal Lubricant Performance, Professional Staff & Service*

## **HB-1240 SYNTHETIC MV ATF TES 295**

### **DESCRIPTION:**

**HB-1240 SYNTHETIC MV ATF TES 295** is manufactured from synthetic base stocks with additive technology that offers reliable multi-vehicle performance. This product provides frictional properties, wear protection, and fluid characteristics required by most heavy-duty automatic transmissions. It is formulated to sustain the demands of extreme operating conditions and retain both high temperature fluid durability and low temperature fluidity. This product is designed for use in heavy-duty automatic transmissions in trucks and buses, waste collection trucks, bus fleets and transit vehicles. It is recommended for use in applications where the OEM specifies a fluid providing performance capabilities comparable to Allison TES-295, C-4, or TES-389.

### **APPLICATIONS:**

**HB-1240 SYNTHETIC MV ATF TES 295** is recommended for heavy-duty application where an OEM specifies an Allison TES-295, C-4, or TES-389. It is also recommended in passenger car transmissions, including those previously serviced by GM DEX-III (H) and Ford MERC brands or requiring a Ford MERC-V fluid performance level. Demanding automotive applications such as taxi cabs, police cars, delivery trucks, recreational vehicles, and tow trucks will gain added protection, extended service intervals and extend the service life of critical transmission components. Always consult your owner's manual where specific transmission fluids are required.

- \* Do NOT use in CVT fluid applications, Dual-Clutch Automatic Transmissions, Ford Type F Fluid applications, or Honda power steering fluid systems.
- \* Applicability of a multi-vehicle automatic transmission fluid should be checked with the owner's manual for specific vehicle suitability.
- \* This product does not carry a license by any OEM but has good data to support performance in the listed specifications.

### **H & B Industries, Inc.**

9758 Abernathy  
Dallas, TX. 75220  
(214) 350-1984  
[info@hbbind.com](mailto:info@hbbind.com)  
Website [www.hbbind.com](http://www.hbbind.com)

### **H & B Industries, Inc**

301 Crickett Lane  
Temple, TX. 76501  
(254) 985-2525  
[hbsupply@hbbind.com](mailto:hbsupply@hbbind.com)  
Website [www.hbbind.com](http://www.hbbind.com)

# Product Data Sheet

## Typical Properties

Appearance	Red, dyed
Viscosity, cSt	
At 40°C	35.2
At 100°C	7.0
Viscosity Index	165
Brookfield Viscosity, cP@-40C	9,900
Flash Point, (COC °F(°C)	430(221)
Pour Point, °F(°C)	-50(-46)
Gravity, API°	34.2
Specific Gravity, 60°/60°F	0.8540
Density, lbs/Gal	7.11

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification.

Variations that do not affect the performance of the product during the normal manufacturing process.