

Product Data Sheet



Premium Lubricant Products, Optimal Lubricant Performance, Professional Staff & Service

HB-1164 SEAMER OIL FG 150

DESCRIPTION:

SEAMER OIL FG 150 is manufactured with the highest quality white mineral oils and is compounded with anti-wear, anti-weld, dispersant additives, rust and oxidation inhibitors, all of which complement the unsurpassed lubricating ability of the H1 food grade white mineral oil and synthetic lubricating fluids.

SEAMER OIL FG 150 is recommended for can seamers with once through oil systems as well as those that utilize oil recirculating filtration systems.

APPROVALS:

SEAMER OIL FG 150 complies with FDA 21 CFR 178.3570, NSF registration, Kosher certificate, and allergen statements are available upon request.

TYPICAL SPECIFICATIONS:

Color	Off-White
ISO Viscosity Grade	150
Density (LB/GAL)	8.33
Viscosity (cSt @ 40°C, ASTM D-445)	150
Viscosity Index (ASTM D-2270)	95
Flash Point (ASTM D-92)	>400°F
Fire Point (ASTM D-92)	>500°F
Pour Point (ASTM D-97)	>0°F

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification.
Variations that do not affect the performance of the product during the normal manufacturing process.

H & B Industries, Inc.
9758 Abernathy
Dallas, TX. 75220
(214) 350-1984
info@hbind.com
Website www.hbind.com

H & B Industries, Inc.
301 Crickett Lane
Temple, TX. 76501
(254) 985-2525
hbsupply@hbind.com
Website www.hbind.com