

Product Data Sheet



Premium Lubricant Products, Optimal Lubricant Performance, Professional Staff & Service

HB-1200 DURAFILM SYNTHETIC MULTIGRADE PCMO

Passenger Car Motor Oil API SP

SAE GRADES 0W-16, 0W-20, 0W-30, 5W-20, 5W-30, 10W-30

DESCRIPTION:

HB-1200 SYNTHETIC MULTIGRADE PCMO's are formulated to provide outstanding engine protection and performance under severe operating conditions. These are blended from synthetic base stocks and compounded with additive chemistry to deliver superior deterrence against wear and corrosion, restrict oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits. These multigrade oils may be used over an extreme temperature range to permit easier cold weather starting and help minimize engine friction at start-up. These also provide added protection at higher-than-normal engine operating temperatures.

APPLICATIONS:

Recommended for all major automotive gasoline engines, including those equipped with superchargers, used in passenger cars, light trucks, power boats, motorcycles and other mobile equipment performing under extreme temperatures and demanding operating situations. These oils can also be used in a variety of commercial, industrial, and special mechanical system applications. All SAE Grades are backward compatible with API Service Categories SP, SN, SM, SL, SJ/CF (Except for 0W-16 SP/GF-6B).

H & B Industries, Inc.

9758 Abernathy
TX. 75220
(214) 350-1984
info@hbbind.com
Website www.hbbind.com

H & B Industries, Inc

301 Crickett Lane
Temple, TX. 76501
(254) 985-2525
hbsupply@hbbind.com
Website: www.hbind.com

Product Data Sheet

Typical Properties

SAE Grade	0W-16	0W-20	0W-30	5W-20	5W-30	10W-30
API / ILSAC Category	SP/GF-6B	SP/GF-6A	SP/GF-6A	SP/GF-6A	SP/GF-6A	SP/GF-6A
Viscosity, cSt						
At 40° C	35.4	48.0	61.2	48.4	60.4	64.3
At 100° C	7.1	8.9	11.04	8.7	10.6	10.4
Viscosity Index	168	168	175	160	167	150
Cold Cranking, cP -35°C	max 6200	max 6200	max 6200			
Cold Cranking, cP -30°C -25°C				max 6600	max 6600	max 7000
Flash Point, (COC) °C(°F)	221(430)	221(430)	221(430)	227(440)	227(440)	227(440)
Pour Point, °C(°F)	-43(-45)	-43(-45)	-43(-45)	-40(-40)	-40(-40)	-39(-38)
Neut. No., ASTMD-2896	7.5	7.5	7.5	7.5	7.5	7.5
Gravity, API @ 60° F	34.0	33.5	33.5	33.0	32.3	32.0
Sulfated Ash, %wt.	<1.0	<1.0	<1.0	<1.0	<1.0	

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification.

Variations that do not affect the performance of the product during the normal manufacturing process.

H & B Industries, Inc.

9758 Abernathy Dallas,
TX. 75220
(214) 350-1984
info@hbind.com
Website www.hbind.com

H & B Industries, Inc

301 Crickett Lane
Temple, TX. 76501
(254) 985-2525
hbsupply@hbind.com
Website www.hbind.com