

Product Data Sheet



Premium Lubricant Products, Optimal Lubricant Performance, Professional Staff & Service

HB-1106 FLEETLUBE SYNTHETIC BLEND HDMO 10W-30 MULTIGRADE CK-4

DESCRIPTION:

Fleetlube Synthetic Blend Heavy Duty Motor Oil (HDMO) 10W-30 Multigrade, API CK-4, is the most current formulated heavy duty motor oil for all-season use in highway commercial diesel engines, including EGR equipped engine emission-controlled systems. This product is manufactured from selected quality base stocks with additive technology to provide engine protection for current EPA exhaust particulate emissions standards using Ultra-Low Sulfur Diesel (ULSD). It meets current performance requirements for all naturally aspirated, turbocharged and supercharged, diesel engines as well as all four-cycle gasoline engines. This product reflects API CI-4 Plus test improvements in reducing aeration, better oxidation stability, enhanced soot control, and advanced wear protection.

This product meets API current service classifications CH-4, CI-4, CI-4 Plus, CJ-4, and CK-4 and ACEA European Oil Sequences Section E-7-12 & E-9-12. The product satisfies the following engine manufacturer requirements where a SAE 10W-30 is recommended: Mack EO-0 Premium Plus, Mack EOS-4.5, Renault VI RLD-3, Renault VI RLD-4, Caterpillar ECF-3, Cummins CES 20081, Cummins CES 20086, Detroit Diesel DDC93K218, Detroit Diesel DDC93K222, JASO DH-2, MB-228.31, MAN M3575, MTU 2.1, Deutz DQC III-10 LA, Ford WSS- M2C171-E, Ford WSS-M2C171-F1 Volvo VDS-4, and Volvo VDS-4.5.

APPLICATIONS:

Recommended for all major diesel and mixed fleet (diesel/four-cycle gasoline) engine operations in all service and under all operating conditions where the equipment owner specifies the additional performance benefits of multigrade oils. This product is preferable for newer diesel engines with EGR systems and those equipped with Diesel Particulate Filter (DPF) and Diesel Oxidation Catalyst (DOC) technologies.

H & B Industries, Inc.
9758 Abernathy
Dallas, TX. 75220
(214) 350-1984
info@hbbind.com
Website www.hbbind.com

H & B Industries, Inc
301 Crickett Lane
Temple, TX. 76501
(254) 985-2525
hbsupply@hbbind.com
Website www.hbbind.com

Product Data Sheet

	Typical Properties
SAE Grade, Automotive	10W-30
Viscosity, cSt	
At 40° C	76.38
At 100° C	11.5
Viscosity Index	145
Viscosity, CCS, D-5293, -20°C/cP	6350
Flash Point, (COC), °C/°F	221/430
Pour Point, °C/°F	-33/-29
Sulfated Ash, %wt	1.0
Neutralization No., TBN-E	9.2
HTHS, Vis/cP, D-4683	3.5
Gravity, API @ 60° F	30.5

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification.

Variations that do not affect the performance of the product during the normal manufacturing process.