

# Product Data Sheet



## DESCRIPTION:

**HB-1057a Mold/Form release oil** is a heavy-duty concrete release agent for use with molds, metal and/or wooden poly forms used in severe service concrete work. This product is amber in color and enhances mold and form separation in difficult or complex concrete pours. This product enhances corrosion protection and acts as a wetting agent to assist with the application of the product. This product can be applied by spray, brush, swab, or dipping. It is foam resistant to ensure the integrity of the protective film during pressure spraying application. This product can cover 800 to 1000 sq. ft. per gallon on molds, steel and poly forms, 600 to 800 sq. ft. per gallon on wooden forms.

## TYPICAL PROPERTIES

Product Number	HB-1057a
Specific Gravity	0.848
Density, Pounds per Gallon	7.05
Flash Point, COC, ASTM D92, °C (°F)	179 (357)
Pour Point, ASTM D97, °C (°F)	-24 (-13)
Color	Amber
Viscosity, ASTM D445, CSt. @ 40°C	13.1

**H & B Industries, Inc.**  
9758 Abernathy  
Dallas, TX. 75220  
(214) 350-1984  
[info@hbind.com](mailto:info@hbind.com)  
Website: [www.hbind.com](http://www.hbind.com)

**H & B Industries, Inc**  
301 Crickett Lane  
Temple, TX. 76501  
(254) 985-2525  
[hbsupply@hbind.com](mailto:hbsupply@hbind.com)  
Website [www.hbind.com](http://www.hbind.com)