Product Data Sheet



HB-1121 PREMIUM TRACTOR Hydraulic Fluid

DESCRIPTION:

HB-1121 TRACTOR HYDRAULIC FLUID (J20C) is a high-quality lubricant containing antirust, anti-foam and oxidation inhibitors plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. This product is an "all-seasonal" type of oil that resists thickening in cold weather and thinning in the summer heat. This product is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration. Operators, especially farmers, will appreciate the multi-purpose application of this product for transmissions, final drives, and hydraulic systems of tractors thereby eliminating the requirement to stock a variety of oil products.

APPLICATIONS:

Formulated and recommended for multipurpose use in transmissions, differentials, hydraulic and power steering units in many different makes of tractors and farm equipment. This product can be used for those hydraulic, wet brake, and transmission applications where the following OEM fluids are recommended:

Product Data Sheet

AGCO: (Deutz-Allis) - PF-821XL, AC-257541AC-272843.

(Power Fl. 821)

Allison: C-3, C-4

Case-IH: Hy-Trans, Hy-Trans Plus, Hy Trans Ultra MAT-3505, MS-1210, MS-1207/1209,

JIC-144/145

Caterpillar TO-2* & MTO

John Deere J20C, J21A, J14B/C

ABEX/Dennison HF-0, HF-1, HF-2 (Pumps

Only) Ford: ESN-M2C41-B, M2C134-

D/FNHA-2-C-201.00

Hesston/Fiat: AF-87, OT Multi-F

Volvo WB-101/BM

ZF TE-ML-03E

International Harvester: B6 Kubota: UDT Fluid, UDT Super

Massey Ferguson M-1141(Permatron

III) M-1143, M-1145

Minneapolis-Moline: Q-1766, Q-1766B Steiger SEMS 17001**

Sundstrand HMS 103 White Equip.

Q-1722

White Q 1826 & Type 55 (See AGCO) Renk Doromat: 874A/B Versatile (now New Holland)

23M,24M

Vickers M-2950-S, I-286-S

Premium Tractor Hydraulic Fluid is not recommended for Cat T0-4 service.

Use Drive Train TC of the appropriate viscosity.

Hydraulic Trans Fluid: Gear, Hydraulic and Wet Brake Oil.

*** Farm tractor applications only; not for extreme temperatures or severe operations.

Typical Properties

SAE Grade Automotive

Gear

Viscosity, cSt

At 40°C

At 100°C

Viscosity, SUS

At 100°F

At 210°F Viscosity Index

Flash Point, Deg C/(F) (min)

Pour Point, Deg C/(F)

Gravity, API @ 60°F

Density, lbs/gallon

1<mark>0W-2</mark>0 (Approx)

75

55

9.2

28357

140 (Minimum)

200(392)

-40(-40)

28.2

7.38

H & B Industries, Inc.

9758 Abernathy Dallas, TX. 75220 (214) 350-1984 info@hbind.com Website www.hbind.com H & B Industries, Inc 301 Crickett Lane Temple, TX. 76501 (254) 985-2525 hbsupply@hbind.com Website www.hbind.com