

## Product Data Sheet



# HB-556 SUPER LUBE HIGH TEMP

## H1 FOOD GRADE GREASE

### DESCRIPTION:

- USDA H-1 Food Grade, for incidental contact with food
- NLGI grade 2 heavy duty multi-purpose grease with PTFE
- Longer life protection against friction, wear, rust and corrosion
- Machinery lasts longer, downtime is reduced and productivity is increased
- Will not run or drip, does not evaporate or form gummy deposits and will not melt or separate
- Synthetic, heavy-duty
- Outlasts conventional greases
- Compatible with most other lubricants
- Clear Non-staining

### BENEFITS:

- USDA H-1 food grade rating
- Clean, non-toxic
- Dielectric
- Will not drip, run or evaporate
- Impervious to salt water, safe in potable water
- Long lasting
- Prevents rust and corrosion while reducing friction
- Wide temperature range -45°F to 450°F
- Kosher Approved

### APPLICATIONS:

- Food processing equipment conveyors and chains
- Plain, anti-friction, ball, roller, wheel bearings
- Cams, slides, valves, caliper assembly and bearing grease
- Hubs, axles, chassis, shocks, springs, seat regulators & tracks
- Dielectric grease
- Linkage, hinges, locks
- Garage doors, faucets, pool pumps
- Farm equipment, seat regulators & tracks, fifth wheels

#### H & B Industries, Inc.

9758 Abernathy  
Dallas, TX. 75220  
(214) 350-1984  
[info@hbind.com](mailto:info@hbind.com)  
Website [www.hbind.com](http://www.hbind.com)

#### H & B Industries, Inc

301 Crickett Lane  
Temple, TX. 76501  
(254) 985-2525  
[hbsupply@hbind.com](mailto:hbsupply@hbind.com)  
Website [www.hbind.com](http://www.hbind.com)

# Product Data Sheet

## Typical Properties

Color:	Translucent White
Consistency Grade (ASTM D1092):	NLGI-2
Dropping Point (ASTM D556):	>500°F (206.C)
Wheel Bearing Leakage (ASTM D-1263):	.2g
Rust Prevention:	Pass
Copper Corrosion (ASTM D-4048):	24 hrs @ 100 C, 1B, shiny
Four-Ball Load Wear Index (ASTM D-2783):	81.73 kg
Four-Ball EP Weld Point (ASTM D-2783):	400 kg
PTFE Fortified:	Yes
USDA Category:	H1

**CAUTION:** Do not ingest. If this should occur, drink large volumes of water and seek medical attention. Avoid storage of product in freezing temperatures. Keep container sealed when not in use. Rinse empty container before discarding in an authorized landfill site. **KEEP OUT OF REACH OF CHILDREN.**

### **H & B Industries, Inc.**

9758 Abernathy  
Dallas, TX. 75220  
(214) 350-1984  
[info@hbind.com](mailto:info@hbind.com)  
Website [www.hbind.com](http://www.hbind.com)

### **H & B Industries, Inc**

301 Crickett Lane  
Temple, TX. 76501  
(254) 985-2525  
[hbsupply@hbind.com](mailto:hbsupply@hbind.com)  
Website [www.hbind.com](http://www.hbind.com)