

Product Data Sheet



HB-1112 LUBRAFILM OIL CONDITIONER

DESCRIPTION:

- A highly viscous oil supplement which contains a shear-stable viscosity index improver to beef up any oil's film strength and the ability to keep engines cleaner.
- Contains a concentrate of Moly-G which will give armor-plate protection to any oil, including motor oils, gear oils and oils for other applications.

COMPOSITION:

Combines a highly refined viscosity index improver with a wide variety of stabilizing agents such as:

Acid-
Neutralizers
Anti-Wear
Additives Anti-
Foam Agents

Oiliness Additives
Corrosion Inhibitors
Thermal Stability Agents

Lubrafilm helps any oil's ability to maintain proper viscosity under high heat conditions and contains components to reduce carbon and engine wear.

PERFORMANCE CHARACTERISTICS:

Controls Consumption
Removes Engine
Deposits Improves
Power
Neutralizes Harmful
Engine Acids Improves
Compression Prevents
Excessive Wear

Reduces Blow-By
Reduces Lifter & Valve Noise Reduces
Frictional Drag
Seals Rings Better
Increases Oil Pressure
Reduces Piston Scuffing & Scoring

USES

Especially recommended for use with all motor oils in:

Diesel Engines
Gasoline Engines Compressors
Air Cooled Engines
LPG Engines
Natural Gas Engines
Final Drives

Manual Transmissions
Differentials
Speed Reducers
Transfer Cases
Hydraulic Systems

TYPICAL APPLICATIONS:

Farm Tractors
Farm Implements
Power Plants
Industrial Plants
Logging Equipment
Boats

Heavy Duty Trucks
Stationary Engines
Excavators
Fork Lifts
Drilling Rigs
Oil Production Engines

SPECIFICATIONS:



| | |
|-----------------------|------------|
| Viscosity, SUS | |
| @100°F | 25000 |
| @210°F | 2100 |
| Viscosity, Cst | |
| @100°F | 5000 |
| @210°F | 450 |
| Specific Gravity | 0.85 |
| Color ASTM | Dark Green |
| Flash Point | 140°F |
| Pour Point | -5°F |
| Acid Test | Excellent |
| 1-H Test (M2C 1010 B) | Pass |
| Piston Skirt | 9.0 |
| Varnish (10=clean) | |